

Roof hatch: Model AG

As manufactured by:

Grillage Bolar (Canada) Inc.
50 Omer de Serres
Blainville, Québec
J7C 5H2

Tel: 450-435-7385 OR 1-800-552-6527
Fax: 450-435-3600 OR 1-800-667-3660

Website: www.bolar.com
E-Mail: sales@bolar.com

Specifications for model AG

The model AG roof hatch is fabricated with natural 11-gauge (3.20 mm) aluminum for the cover and 14-gauge (1.99 mm) aluminum for the cover lining. As for the base, it is made of galvanized steel of 14-gauge (1.99 mm) according to ASTM A653 standard and coated with a layer of primer paint.

The standard insulation rating for this model of roof hatch is R4. Upon request, the manufacturer can produce and increase the complete insulation of the roof hatch to achieve higher insulation ratings, up to a maximum of R42.

The base of the model A roof access hatch is 12" (305 mm) in height and has a peripheral flange of 3 9/16" (90mm) at the bottom, which serves as a seating for the hatch. This flange is perforated at the four corners of a hole of 3/8" (9.5mm) and is used to safely secure the hatch to the roof.

The cover of the model AG roof hatch opens at an angle of more or less 90 degrees.

The entirety of this roof hatch is reinforced at necessary points to accommodate hardware and built to cover the entire base and its water discharge.

Characteristics

The roof hatch model AG is always equipped with two telescopic cylinders to counterbalance the weight of the cover(s).

This model is fitted with two stainless steel hinges with 5/16" X 3" (8mm X 75mm) rods serving as pivots.

Fabricated from steel with one or more hold open operating arms and covered with a yellow zinc coating, this roof hatch also features a one-handed operable exterior handle covered with a red vinyl grip for enhanced traction.

For the single-leaf roof hatch, the interior handle assembly includes a chrome handle, a latch lock, and a padlock hasp. For the double-leaf roof hatch, the sets of locks are replaced by two lockset system each having a double attachment secured to the base.

This model is also equipped with a neoprene seal, which assures a tightness to the joint of the cover(s) and to the base of the hatch, forming a weatherproof unit.

Warranty

The roof hatch model AG by Grillage Bolar is guaranteed against any manufacturing defects for a period of 1 year, subject to proper use.

Installation

The installation of Grillage Bolar roof hatch must be secured to the building's framework at a suitable level to prevent any warping to the prefabricated frame of the roof hatch.

50, Omer-Deserres, Blainville Qc. J7C 5H2

P. 450.435.7385 TF. 1.800.552.6527 F. 450.435.3600

BOLAR.COM

commercial
institutional
industrial
residential